



Revision	REV-02
Issue date	07.08.2026

TECHNICAL DATA SHEET

PEARL OIL NACERA 0W-20 DPF

0W-20 |

NACERA 0W-20 DPF is an advanced SAE 0W-20 passenger-car engine oil developed for modern gasoline and diesel applications where exhaust after-treatment compatibility and dependable protection are important. It provides stable lubrication across a wide temperature range, helps limit wear and deposit formation, and supports the cleanliness of critical engine components. The product is intended for vehicles requiring the MEETS & EXCEEDS performance levels listed for this grade.

MEETS & EXCEEDS

- | | |
|--|---|
| <ul style="list-style-type: none">• ACEA C5• VW 508 00 / 509 00 | <ul style="list-style-type: none">• Porsche C20 |
|--|---|

TDS - TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUE
Density @15°C	ASTM D4052	0.86 - 0.87 g/cm ³
Kinematic Viscosity @100°C	ASTM D445	6.9 - 9.3 cSt
Viscosity Index	ASTM D2270	Min. 140
Flash Point	ASTM D92	Min. 220 °C
Pour Point	ASTM D97	Max. -30 °C

Typical values are indicative technical properties and are not specification limits.