



Revision	REV-02
Issue date	07.08.2026

TECHNICAL DATA SHEET

PEARL OIL LEGARA 10W-40 SL

10W-40 |

LEGARA 10W-40 SL is a robust SAE 10W-40 engine oil developed for gasoline, LPG and suitable diesel engines. It forms a durable lubricating film on critical components to help reduce wear and maintain protection under high temperatures and demanding operating conditions. The formulation supports viscosity stability, deposit and sludge control, and dependable daily performance for vehicles requiring the listed legacy API / OEM performance levels.

MEETS & EXCEEDS

• API SM/CF	• ACEA A3/B4
• MB 229.1	• VW 501.01 / 505.00
• Renault RN 0700 / RN 0710	• Fiat 9.55535-D2

TDS - TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUE
Density @15°C	ASTM D4052	0.87 - 0.88 g/cm ³
Kinematic Viscosity @100°C	ASTM D445	12.5 - 16.3 cSt
Viscosity Index	ASTM D2270	Min. 130
Flash Point	ASTM D92	Min. 225 °C
Pour Point	ASTM D97	Max. -30 °C

Typical values are indicative technical properties and are not specification limits.