



Revision	REV-02
Issue date	07.08.2026

TECHNICAL DATA SHEET

PEARL OIL LEGARA 15W-40 SL

15W-40 |

LEGARA 15W-40 SL is a robust SAE 15W-40 engine oil developed for gasoline, LPG and suitable diesel engines. It forms a durable lubricating film on critical components to help reduce wear and maintain protection under high temperatures and demanding operating conditions. The formulation supports viscosity stability, deposit and sludge control, and dependable daily performance for vehicles requiring the listed legacy API / OEM performance levels.

MEETS & EXCEEDS

• API SL	• API CF
• ACEA A3/B3	• MB 229.1
• VW 501 01	• VW 505 00

TDS - TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUE
Density @15°C	ASTM D4052	0.867 g/cm ³
Kinematic Viscosity @40°C	ASTM D445	110.0 cSt
Kinematic Viscosity @100°C	ASTM D445	15.0 cSt
Viscosity Index	ASTM D2270	145
Flash Point	ASTM D92	240 °C
Pour Point	ASTM D97	-27 °C
CCS Viscosity	ASTM D5293	7000 cP
MRV Viscosity	ASTM D4684	30000 cP
NOACK Volatility	ASTM D5800	10.0 %
TBN	ASTM D2896	11.0 mgKOH/g
Sulphated Ash	ASTM D874	1.3 %

Typical values are indicative technical properties and are not specification limits.