



|            |            |
|------------|------------|
| Revision   | REV-02     |
| Issue date | 07.08.2026 |

## TECHNICAL DATA SHEET

### PEARL OIL STRATON 5W-40 SN

#### 5W-40 |

STRATON 5W-40 SN is a high-performance SAE 5W-40 engine oil designed for modern gasoline and suitable light-duty diesel engines. It supports rapid lubrication during start-up, maintains viscosity stability under operating heat and helps reduce wear, sludge and deposits. Its balanced protection contributes to clean engine operation, controlled oil consumption and dependable performance in city, highway and mixed driving conditions.

#### MEETS & EXCEEDS

|               |                             |
|---------------|-----------------------------|
| • API SN/CF   | • ACEA A3/B4                |
| • MB 229.5    | • BMW Longlife-01           |
| • Porsche A40 | • Renault RN 0700 / RN 0710 |
| • GM LL-B-025 | • VW 502 00 / 505 00        |

#### TDS - TYPICAL TECHNICAL PROPERTIES

| PROPERTY                   | TEST METHOD | TYPICAL VALUE                 |
|----------------------------|-------------|-------------------------------|
| Density @15°C              | ASTM D4052  | 0.86 - 0.87 g/cm <sup>3</sup> |
| Kinematic Viscosity @100°C | ASTM D445   | 12.5 - 16.3 cSt               |
| Viscosity Index            | ASTM D2270  | Min. 132                      |
| Flash Point                | ASTM D92    | Min. 210 °C                   |
| Pour Point                 | ASTM D97    | Max. -34 °C                   |

Typical values are indicative technical properties and are not specification limits.