



Revision	REV-02
Issue date	07.08.2026

TECHNICAL DATA SHEET

PEARL OIL VELOS ATF CVT

ATF CVT | 1L

VELOS ATF CVT is a high-performance transmission fluid developed for applications matching the listed OEM fluid requirements. Its carefully balanced friction characteristics support smooth engagement and shift quality, while oxidation resistance and viscosity stability help protect gears, bearings, clutches and hydraulic control components over a wide operating-temperature range. Always select the fluid according to the vehicle or transmission manufacturer specification.

MEETS & EXCEEDS

• Toyota CVT Fluid FE	• Toyota/Aisin CVT Fluid TC
• Nissan CVT Fluid NS-3	• Nissan CVT Fluid NS-2
• Mitsubishi SP-CVT Fluid J4	• Mitsubishi CVTF-J1
• Daihatsu Ammix CVTF-DFE	• Suzuki CVT Green 2
• Honda HCF-2	

TDS - TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUE
Density @15°C	ASTM D4052	0.845 - 0.860 g/cm ³
Kinematic Viscosity @100°C	ASTM D445	7.7 cSt
Viscosity Index	ASTM D2270	Min. 160
Flash Point	ASTM D92	Min. 210 °C
Pour Point	ASTM D97	Max. -45 °C

Typical values are indicative technical properties and are not specification limits.